# ilumen





### FEATURING MODULE PANEL LIGHTS

Available in two panel sizes; 600 x 600mm, 300 x 1200mm.

Featuring an output of up to 6400 lm that is carefully controlled to provide low-glare light (UGR <19).

with choice of colour temperature 3000 K, 4000 K, 5000 K, 6500 K.

Suitlable for office & Education



Office



Education










GERMAN QUALITY DEUTSCHE QUALITÄT

#### HIGH LUMEN OUTPUT

Elka features that it's made of reflector that allow glare control (UGR<19) even at very high lumen output. Besides, opal cover solution is also available.



#### **SUPER SLIM**


The thickness of Elka is only 18mm, ideal for lay-in ceilings and help reduce space when it's loaded in container, so that you can save more shipping cost.

#### **SMART CONTROLS**


WITH THE OPTIONAL MICROWAVE SENSOR (MWS). The Elka gains motion switch functionality. No need to remember to turn the lights off. This can turn the panel on when movement is detected within a space, and turn it off again after a pre-selected hold-time when motion ceases.



### PRODUCT PARAMETER



Optics: Opal cover



Optics: Reflector cover

	Optics:Opal cover	Optics: Reflector cover	
Power	36W/40W/48W	36W/40W/48W	
Luminous Flux	3600LM/4400LM	5300LM/6400LM	
Ra	80	80	
UGR	<22	<19	
Light Efficiency	Up to	Up to 130lm/W	
Input voltage	220-	220-240Vac	
Ra	80	80, 90	
Operating Temperature -10°C to +40°C		to +40°C	
Beam angle	75	75°/110°	
IP/IK rating	IP20	IP20/IK05	
SDCM	<	<3	
LED Lifespan	L80B10>60,000Hrs@35Deg		
Panel backplate integr	ated S	SPCC	
Lens	PC PC		
Reflector PC		PC	
Body	Powder coated	Powder coated in white RAL9003	
Mounting options Lay-in ceilings/Recessed/Suspended /Surface mounted		uspended /Surface mounted	

Intelligent control

0-10V/DALI/Microwave sensor/PIR sensor/Bluetooth



## ilumen

© Address: Am Hopfenbach 12, 22926 Ahrensburg, Germany

Sephone: +49 4102 7798707
Separation = mail: info@ilumenled.de

⊕ www.ilumenled.de