ilumen



Matilda

The next generation of high bay light



ELEGANT IP65 SQUARE HIGH BAY

Simplified exterior design, matrix-style fins, which not only fully utilize the heat dissipation function but also reflect an industrial design style.

With power 100W/150W/200W and lumen output 16000lm/23250lm/30000lm

Can be used in Warehouse, Workshop, Supermarket, Exhibition hall



Logistics



Manufacturing



Retail



Industry



Warehouse

Polarized beam angles are optional

110deg



90deg



30*110dea












IP65 rating for front side of fixtures.



Tool-free wiring and installation





DIP switch, 3-power-in-1 (100W/150W/200W)



PRODUCT PARAMETER



Power	100W	150W	200W	
Luminous Flux	16000lm	23250lm	30000lm	
Ra		>80		
Light Efficiency		160lm/w		
Input voltage		220-240Vac		
Beam angle		90°/110°/30*110°		
Operating Temper	rature	-30°C to +50°C		
Ingress protection	code IP	IP65 (Front side), IP54 (Back side)		
LED Lifespan		L80B10>60,000Hrs@35Deg		
Color		Powder white		
Lens materials		PC/PS		
Mounting options	Suspe	Suspending/Ceiling mounted with bracket		
SDCM		<6		



ilumen

© Address: Am Hopfenbach 12, 22926 Ahrensburg, Germany

Sephone: +49 4102 7798707
✓ email: info@ilumenled.de

mww.ilumenled.de