

Kroos

The next generation of flood light



GENERAL

Aluminium material whose capability of heat dissipation is superior.

Symmetrical and asymmetrical optics for stadium, seaport, airport, train station.

Tempered Glass cover.

Ultra-high brightness Lighting Chips which could up to 170 lm/W.

Tilt Angle bracket design, convenient terminal installation and debugging.

LED modular engine and easy for replacement and maintenance.

Weight control and make sure it is safe and pass 3G vibration.

DALI/DMX control available.



Sport fields



Industrial area



Airport





Harbor







VERSIONS







400W














PRODUCT DATA

Light and Electrical

LED Chip Lumileds

Light Efficacy 145lm/w, 150lm/w, 160lm/w CCT 4000K/ 5000K/ 5700K

CRI 70

LED Lifespan 96,000h@L80B10

Driver Philips 220-240Vac Input voltage Input Frequency 50/60Hz

Inrush current >0.93 Power Factor THD <15

SPD 10KV/20KV (optional)


CLASS

Intelligent Control

Photometric distributions

(60deg)

(30deg)



(90deg)



(polarized 50deg)



Optional

Operating Tempreture Controls and Dimming

Operating Temperature Dimmable

Mechanical and Housing

Structure Material Die-cast Aluminum EN

ADC-12

0-10V Dimming, DMX512, DALI

Powder coated Finish Material (PC)Polycarbonate Lens Material

Glass Material

IP66 Ingress protection code IK08 Mech. impact protection

Certificates and Standards





RoHS

-30°C~+50°C

ErP



KEY BENEFITS





CBU Completely-built-up

Fully assembled lamps

Prepared for shipping to clients

Direct shipping to end-user from client's warehouse without additional processing

SKD Semi-knocked-down

Complete lamps kit at different assembly levels

Small-scale assembly is required at clients' site

Flexible adjustment to satisfy all the needs from different projects









O Address: Am Hopfenbach 12, 22926 Ahrensburg, Germany

Sephone: +49 4102 7798707Sepaid: info@ilumenled.de

www.ilumenled.de